

310200002 - CATALIZADOR EPOXI 1330 SD COMPONENTE B



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** 310200002 - CATALIZADOR EPOXI 1330 SD COMPONENTE B
Other means of identification:
UFI: 8UP9-D0U2-700D-PDY8
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses (Consumer use): Industrial paint
Relevant uses (Professional users): Industrial paint
Relevant uses (Industrial user): Industrial paint
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
EUPINCA
C/ Londres, 13 - Pol. Ind. Cabezo Beaza
30353 Cartagena - Murcia - España
Phone: +34 968089000
info@grupotkrom.com
https://www.tkrom.com/
- 1.4 Emergency telephone number:** +34 968 08 90 00 (Office hours)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302
Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400
Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410
Eye Dam. 1: Serious eye damage, Category 1, H318
Skin Corr. 1C: Skin corrosion, Category 1C, H314
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Acute Tox. 4: H302 - Harmful if swallowed.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Eye Dam. 1: H318 - Causes serious eye damage.
Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P264: Wash thoroughly after handling.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501: Dispose of contents/container according to the separated collection system used in your municipality.

Substances that contribute to the classification

Fatty acids C18 unsat, reaction products with triethylenetetramine; Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine; benzyl alcohol; 3-aminopropyl dimethylamine

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B****SECTION 2: HAZARDS IDENTIFICATION (continued)****2.3 Other hazards:**

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substance:**

Not relevant

3.2 Mixture:**Chemical description:** Mixture composed of pigments and resins**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 1226892-44-9 EC: 629-765-4 Index: Not relevant REACH: 01-2119490750-36-XXXX	Fatty acids C18 unsat, reaction products with triethylenetetramine⁽¹⁾	Self-classified	50 - <75%
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317 - Danger	
CAS: 68082-29-1 EC: 500-191-5 Index: Not relevant REACH: 01-2119972320-44-XXXX	Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine⁽¹⁾	Self-classified	25 - <50%
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1A: H317 - Danger	
CAS: 100-51-6 EC: 202-859-9 Index: 603-057-00-5 REACH: 01-2119492630-38-XXXX	benzyl alcohol⁽¹⁾	ATP ATP21	10 - <25%
	Regulation 1272/2008	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Sens. 1B: H317 - Warning	
CAS: 90-72-2 EC: 202-013-9 Index: 603-069-00-0 REACH: 01-2119560597-27-XXXX	2,4,6-tris(dimethylaminomethyl)phenol⁽¹⁾	ATP CLP00	1 - <2.5%
	Regulation 1272/2008	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	
CAS: 109-55-7 EC: 203-680-9 Index: Not relevant REACH: 01-2119486842-27-XXXX	3-aminopropyldimethylamine⁽¹⁾	ATP CLP00	1 - <2.5%
	Regulation 1272/2008	Acute Tox. 4: H302; Flam. Liq. 3: H226; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
Fatty acids C18 unsat, reaction products with triethylenetetramine	Acute	1
CAS: 1226892-44-9 EC: 629-765-4	Chronic	10

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	LD50 oral	1200 mg/kg	Rat
	LD50 dermal	Not relevant	
	LC50 inhalation vapour	Not relevant	
3-aminopropyldimethylamine CAS: 109-55-7 EC: 203-680-9	LD50 oral	1870 mg/kg	Rat
	LD50 dermal	Not relevant	
	LC50 inhalation vapour	Not relevant	
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	1200 mg/kg	
	LD50 dermal	Not relevant	
	LC50 inhalation vapour	Not relevant	

SECTION 4: FIRST AID MEASURES

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B****SECTION 4: FIRST AID MEASURES (continued)****4.1 Description of first aid measures:**

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and also risk damage to the respiratory system through inhalation. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EEC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

- CONTINUED ON NEXT PAGE -



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Fatty acids C18 unsat, reaction products with triethylenetetramine CAS: 1226892-44-9 EC: 629-765-4	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0,1 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0,492 mg/m ³	Not relevant
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine CAS: 68082-29-1 EC: 500-191-5	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	1,1 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	3,9 mg/m ³	Not relevant
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	40 mg/kg	Not relevant	8 mg/kg	Not relevant
	Inhalation	110 mg/m ³	Not relevant	22 mg/m ³	Not relevant
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	0,15 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0,53 mg/m ³	Not relevant
3-aminopropyldimethylamine CAS: 109-55-7 EC: 203-680-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	1,2 mg/m ³	Not relevant

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Fatty acids C18 unsat, reaction products with triethylenetetramine CAS: 1226892-44-9 EC: 629-765-4	Oral	Not relevant	Not relevant	0,05 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,05 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0,09 mg/m ³	Not relevant
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine CAS: 68082-29-1 EC: 500-191-5	Oral	Not relevant	Not relevant	0,56 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,56 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0,97 mg/m ³	Not relevant
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Oral	20 mg/kg	Not relevant	4 mg/kg	Not relevant
	Dermal	20 mg/kg	Not relevant	4 mg/kg	Not relevant
	Inhalation	27 mg/m ³	Not relevant	5,4 mg/m ³	Not relevant
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	Oral	Not relevant	Not relevant	0,075 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,075 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	0,13 mg/m ³	Not relevant

PNEC:

Identification					
Fatty acids C18 unsat, reaction products with triethylenetetramine CAS: 1226892-44-9 EC: 629-765-4	STP	5,57 mg/L	Fresh water	0,0254 mg/L	
	Soil	9,44 mg/kg	Marine water	0,00254 mg/L	
	Intermittent	0,00294 mg/L	Sediment (Fresh water)	99,4 mg/kg	
	Oral	0,002 g/kg	Sediment (Marine water)	9,94 mg/kg	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine CAS: 68082-29-1 EC: 500-191-5	STP	3,84 mg/L	Fresh water	0,004 mg/L	
	Soil	86,78 mg/kg	Marine water	0 mg/L	
	Intermittent	0,043 mg/L	Sediment (Fresh water)	434,02 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	43,4 mg/kg	
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	STP	39 mg/L	Fresh water	1 mg/L	
	Soil	0,456 mg/kg	Marine water	0,1 mg/L	
	Intermittent	2,3 mg/L	Sediment (Fresh water)	5,27 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,527 mg/kg	

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	STP	0,2 mg/L	Fresh water	0,046 mg/L
	Soil	0,025 mg/kg	Marine water	0,005 mg/L
	Intermittent	0,46 mg/L	Sediment (Fresh water)	0,262 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,026 mg/kg
3-aminopropyldimethylamine CAS: 109-55-7 EC: 203-680-9	STP	10 mg/L	Fresh water	0,073 mg/L
	Soil	0,104 mg/kg	Marine water	0,007 mg/L
	Intermittent	0,34 mg/L	Sediment (Fresh water)	0,735 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,073 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	 CAT III	EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Butyl)	 CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield	 CAT II	EN ISO 16321-1:2022 + EN ISO 16321-3:2022 EN ISO 18526-(1,2,3,4):2020 EN ISO 18526-(1,2,3,4):2020 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks	 CAT III	EN 13034:2005+A1:2009 EN ISO 18526-(1,2,3,4):2020 EN ISO 13982-1:2004/A1:2010 ISO 6529:2013 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk	 CAT III	EN ISO 20345:2022 EN 13832-1:2018	Replace boots at any sign of deterioration.

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	1 % weight
V.O.C. density at 20 °C:	9,55 kg/m ³ (9,55 g/L)
Average carbon number:	5
Average molecular weight:	102,2 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	152,78 kg/m ³ (152,78 g/L)
EU limit for the product (Cat. A.J):	500 g/L (2010)
Components:	Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Characteristic
Colour:	According to the markings on the package
Odour:	Characteristic
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	199 °C
Vapour pressure at 20 °C:	29 Pa
Vapour pressure at 50 °C:	242,27 Pa (0,24 kPa)
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	954,9 kg/m ³
Relative density at 20 °C:	0,955
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Relative vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *
Flammability:	
Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	401 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *
Particle characteristics:	
Median equivalent diameter:	Not relevant *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B****SECTION 11: TOXICOLOGICAL INFORMATION (continued)****Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, if it is swallowed causes burns destroying the tissues. For more information about secondary effects from skin contact see section 2.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Not relevant
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	LD50 oral	1200 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour		
3-aminopropylidimethylamine CAS: 109-55-7 EC: 203-680-9	LD50 oral	1870 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour		

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B**



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	1200 mg/kg	
	LD50 dermal		
	LC50 inhalation vapour		

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Very toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
Fatty acids C18 unsat, reaction products with triethylenetetramine CAS: 1226892-44-9 EC: 629-765-4	LC50	0,19 mg/L (96 h)	Danio rerio	Fish
	EC50	0,18 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0,476 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine CAS: 68082-29-1 EC: 500-191-5	LC50	Not relevant		
	EC50	Not relevant		
	EC50	0,15 mg/L (72 h)	Raphidocelis subcapitata	Algae
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	LC50	345 mg/L (96 h)	QSAR	Fish
	EC50	Not relevant		
	EC50	Not relevant		
3-aminopropyldimethylamine CAS: 109-55-7 EC: 203-680-9	LC50	122 mg/L (96 h)	Leuciscus idus	Fish
	EC50	68,3 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	56,2 mg/L (72 h)	Scenedesmus subspicatus	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Fatty acids C18 unsat, reaction products with triethylenetetramine CAS: 1226892-44-9 EC: 629-765-4	NOEC	Not relevant		
	NOEC	0,27 mg/L	Daphnia magna	Crustacean
3-aminopropyldimethylamine CAS: 109-55-7 EC: 203-680-9	NOEC	Not relevant		
	NOEC	3,64 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Fatty acids C18 unsat, reaction products with triethylenetetramine CAS: 1226892-44-9 EC: 629-765-4	BOD5	Not relevant	Concentration	150 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	22,7 %
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	94 %

12.3 Bioaccumulative potential:

Substance-specific information:

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B****SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Bioaccumulation potential	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine CAS: 68082-29-1 EC: 500-191-5	BCF	
	Pow Log	5
	Potential	
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BCF	1
	Pow Log	1.05
	Potential	Low
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	BCF	3
	Pow Log	0.77
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Fatty acids C18 unsat, reaction products with triethylenetetramine CAS: 1226892-44-9 EC: 629-765-4	Koc	940000	Henry	Not relevant
	Conclusion	Immobile	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine CAS: 68082-29-1 EC: 500-191-5	Koc	1000000000	Henry	Not relevant
	Conclusion	Immobile	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant
benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Koc	15.7	Henry	8,8E-2 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	3,679E-2 N/m (25 °C)	Moist soil	Yes
2,4,6-tris(dimethylaminomethyl)phenol CAS: 90-72-2 EC: 202-013-9	Koc	15130	Henry	9,312E-12 Pa·m ³ /mol
	Conclusion	Immobile	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP13 Sensitising, HP8 Corrosive

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B**



SECTION 14: TRANSPORT INFORMATION (continued)

Transport of dangerous goods by land:

With regard to ADR 2025 and RID 2025:



- 14.1 UN number or ID number:** UN3066
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 8
Labels: 8
14.4 Packing group: III
14.5 Environmental hazards: Yes
14.6 Special precautions for user
Special regulations: 163, 367
Tunnel restriction code: E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
14.7 Maritime transport in bulk according to IMO instruments: Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 42-24:



- 14.1 UN number or ID number:** UN3066
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 8
Labels: 8
14.4 Packing group: III
14.5 Marine pollutant: Yes
14.6 Special precautions for user
Special regulations: 223, 367, 163
EmS Codes: F-A, S-B
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Not relevant
14.7 Maritime transport in bulk according to IMO instruments: Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2026:



- 14.1 UN number or ID number:** UN3066
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 8
Labels: 8
14.4 Packing group: III
14.5 Environmental hazards: Yes
14.6 Special precautions for user
Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- CONTINUED ON NEXT PAGE -

**310200002 - CATALIZADOR EPOXI 1330 SD
COMPONENTE B****SECTION 15: REGULATORY INFORMATION (continued)**

- Article 95, REGULATION (EU) No 528/2012: *benzyl alcohol (100-51-6) - PT: (6)*
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
E1	ENVIRONMENTAL HAZARDS	100,000	200,000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

- H314: Causes severe skin burns and eye damage.
- H318: Causes serious eye damage.
- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.
- H317: May cause an allergic skin reaction.
- H302: Harmful if swallowed.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- Acute Tox. 4: H302 - Harmful if swallowed.
- Aquatic Acute 1: H400 - Very toxic to aquatic life.
- Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
- Eye Dam. 1: H318 - Causes serious eye damage.
- Eye Irrit. 2: H319 - Causes serious eye irritation.
- Flam. Liq. 3: H226 - Flammable liquid and vapour.
- Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
- Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.
- Skin Irrit. 2: H315 - Causes skin irritation.
- Skin Sens. 1: H317 - May cause an allergic skin reaction.
- Skin Sens. 1A: H317 - May cause an allergic skin reaction.
- Skin Sens. 1B: H317 - May cause an allergic skin reaction.

Classification procedure:

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION (continued)

Skin Corr. 1C: Calculation method
Eye Dam. 1: Calculation method
Aquatic Acute 1: Calculation method
Aquatic Chronic 1: Calculation method
Skin Sens. 1A: Calculation method
Acute Tox. 4: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -