



DISOLVENTE 370 EPOXI ESTUFA

SALES FORMAT

25L, 5L, 1L

DESCRIPTION

A solvent blend specially formulated for primers and topcoats based on solvent-borne epoxy resins (one- or two-component), alkyd and acrylic resins, for both air-drying and oven-drying applications.

SCOPE OF APPLICATION

Specifically for thinning epoxy paints. For cleaning tools with products where this is recommended.

PROPERTIES

- High dilution capacity
- High cleaning power
- Average evaporation rate
- Well-balanced, with adequate drying times for both deep penetration and surface drying.

TECHNICAL DATA

CLASSIFICATION		
APPEARANCE	Liquid	
COLOUR	Colourless/Characteristic Transparent	
DENSITY	0.87 ± 0.03 g/ml	ISO 2811-1
REFRACTION INDEX	1,453–1,455	

APPLICATION PROCESS

Application

As a viscosity regulator for application. Add to the varnish or paint in the proportion indicated in the technical data sheet for the product in use, after curing. Stir the mixture by hand or using mechanical means (but slowly) until a completely homogeneous product is achieved. As a solvent for cleaning tools.

ADDITIONAL INFORMATION

Health and safety	For any information regarding safety issues relating to the use, storage, transport and disposal of waste from this product, users should consult the labelling and the latest version of the Safety Data Sheet, which contains physical, ecological and toxicological data, as well as other relevant information on this subject. WASTE: HAZARDOUS. LER: 080111
Storage	The product will remain stable in its original, unopened packaging, at ambient temperatures not exceeding 30°C or falling below 5°C, for 24 months from the date of manufacture. The product must be stored in a cool, dry place, in its original, tightly sealed and undamaged packaging, and protected from frost and direct sunlight.
Tariff heading	TARIC code: 3814 00 90
Note	The data provided in this technical data sheet may be subject to change depending on possible variations in formulation and, in any case, are indicative values only; they do not exempt the user from carrying out the necessary tests to ensure the product is suitable for a specific job.